

US VACUUM PUMPS LLC

USV-15F ROTARY VANE SINGLE STAGE VACUUM PUMP



US VACUUM pump Model USV-15F is a Single stage, Air-cooled, Rotary vane vacuum pump capable of producing an ultimate vacuum to 2 mm Hg (29.8" Hg).

The pump is small and compact yet produces a very generous 15 cfm of inlet pumping capacity. Typical applications include vacuum drying, impregnation, food packaging, vacuum chucking and de-gassing.

Available standard with 120v Starter box with overload, power cord & N. American plug. Other voltages available


TECHNICAL DATA

PUMP TYPE		USV-15F
Pump Displacement	CFM	15
Ultimate Vacuum	Torr	2
Pump Speed	RPM	3500
Oil Capacity	ml	500
Inlet connection	Inch	1/2
Motor-Installed power	HP	1.5
Weight	LBS	42
Noise level	db(A)	72


Vacuum Tank system


- 15 cfm Vacuum pump
- 30 gallon tank
- 2hp Motor
- Inlet Filter
- Starter box
- Vacuum switch with H-O-A operation
- Rubber mounts
- 120V (1-PH)
- Other voltages available





	BILL OF MATERIAL							
NO.	QTY	DESCRIPTION	PART NUMBER					
1	1	VACUUM PUMP MODEL USVØ15F	USV15F					
2	1	ELECTRIC MOTOR 2HP, 115ø230V, 60HZ	EMCPS15B1.25					
3	1	ISOLATION VALVE, BRASS 1/2"	IBVCPS15B.50					
4	1	CHECK VALVE, ALUMINUM 1/2"	CVCPS15B.50					
5	1	PARTICULATE FILTER	VFISL824050					
6	1	TANK, 30 GALLON	US302470					
7	1	STARTER BOX, 120V	MSCPS15B110					





SCALE

- 1. ALL STANDARD UNIT PIPING SHALL BE SCH/40 ASTM A=53 TYPE F C/W 150# ASTM A=197 MALLEABLE IRON THREADED FITTINGS.
- 2. DIMENSION TOLERANCE TO 1/4". 3. CUSTOMER IS RESPONSIBLE FOR PROPER LIFTING
- EQUIPMENT FOR LIFTING SKID.
 4. ANCHOR BOLTS ARE NOT FURNISHED WITH UNIT.

			·				
0	INITIAL RELEASE			JCM	PD	PD	07-APR-20
REV	DESCRIPTION			DWN	CK	APP	DATE
DWN	JCM	07-APR-20	THIS DRAVING AND ALL INFORMATION SHOWN HEREON ARE THE EXCLUSIVE PROPERTY OF US VACUUM PUMPS, LLC. AND	CERTIFIED DRAWING			
CK	PD	07-APR-20	ARE SUBMITTED ON A CONFIDENTIAL BASIS ONLY, THE RECIPIENT AGREES NOT TO REPRODUCE THE DISCLOSURE OF THE	He V/	ACIII	IM D	UMPS, LLC
APP	PD	07-APR-20	DRAVING OR THE INFORMATION DRAVING, TO RETURN IT UPON REQUEST, AND THAT NO SHOWN HEREON VILL BE MADE TO THE	UO VA	icut	JIVI F	UIVIPS, LLC
SCALE NTS		NTS	THIRD PARTY WITHOUT PRIOR WRITTEN CONCENT OF US VACUUM PUMPS, LLC.		PO	BOY	909

DIMENSIONS ARE IN INCHES [mm] WEIGHT IN LBS [kg]

PROJECTION

USV-15F-30 VACUUM PUMP SYSTEM w/ HORIZONTAL RECEIVER P.O. BOX 909 CANTON, TEXAS 75103 PH: 888-416-7466 / FAX: 877-416-7599

DWG. NO. REV USV-15F.30H.115 0