



US VACUUM PUMPS LLC

LRH-15/35/45 DIMENSIONS

BARE SHAFT CONSTRUCTION W/ MECHANICAL SEAL




US VACUUM LRH pumps are Two stage liquid ring vacuum pumps capable of producing a vacuum to 29" Hg . The pumps are available in various materials of construction (FS = Iron/Stainless steel, SS = All stainless steel).

Pumps are provided with threaded connections for service liquid, pump draining, vacuum relief valve and companion flanges. Optional items include inlet check valve, vacuum relief valve, flow control, solenoid valve, vacuum and temperature gauges.

Pumps can also come as completely packaged units using water or water as a seal fluid.

TECHNICAL DATA

PUMP TYPE		LRH 15	LRH 35	LRH 45
Pumping Capacity (@ 25" Hg)	CFM	15	33	44
Speed	RPM	3500	3500	3500
Motor-Installed power	HP	2	3	5
Average service liquid flow	GPM	1.5	1.5	3.5
Noise level at 60 Torr	db(A)	69	69	69
Minimum suction pressure	Torr	25	25	25






DATA BASED ON :
DRY AIR AT 68 °F - 20 °C —————
SATURATED AIR AT 68 °F - 20 °C -----
SERVICE LIQUID WATER
SERVICE LIQUID TEMPERATURE 59 °F - 15 °C
DISCHARGE PRESSURE 1013 mbar

S.S. PUMPS
CAPACITY : -10%

Tol.: 10%

PERFORMANCE DATA
LIQUID RING VACUUM PUMP
PUMP MODEL
LRH-35




DATA BASED ON :
DRY AIR AT 68 °F - 20 °C
SATURATED AIR AT 68 °F - 20 °C
SERVICE LIQUID
SERVICE LIQUID TEMPERATURE
DISCHARGE PRESSURE


S.S. PUMPS
CAPACITY : -10%

PERFORMANCE DATA
LIQUID RING VACUUM PUMP
PUMP MODEL
LRH-45

745	740	730	700	600	500	300	100	mm Hg VACUUM Inches Hg			
29.2	29	28.6	28	27	26	25	20	16	10	6	2



DIMENSIONS



Pump Type	B	E	M	K	Weight lbs.
LRH 15	193	219	139	327	40
LRH 35	243	269	189	377	46

